



Gaska Tape Inc.

A3 Adhesive Specification

GASKA TAPE INC. has developed the pressure sensitive adhesive type A3 for general purpose applications needing an aggressive adhesive which bonds quickly to most surfaces. Its properties are as follows:

Adhesive Type	-	Acrylic (emulsion based)
Adhesive Thickness	-	2.0 mils minimum
Adhesion to Steel ¹	-	2 pounds/inch width minimum

¹ - ASTM D-1000 (on 1 mil polyester film - Note: adhesion will vary depending on carrier and substrate)

Other information

(derived from laboratory testing on polyester film and not included in the specification)

Recommended application range	50°F to 110°F
Recommended temperature range	-30°F to 180°F

Chris Habegger
Technical Director
Revised 2/13/02

Notice: Although the information and recommendations set forth (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, Gaska Tape Inc. makes no representation or warranties as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will Gaska Tape Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information or the product to which Information refers. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and Gaska Tape Inc. makes no representation or warranty, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS. FOR A COPY OF GASKA TAPE'S FULL LIMITED WARRANTY, PLEASE ASK YOUR GASKA TAPE REPRESENTATIVE OR FAX YOUR REQUEST TO 574-293-4504.