

6031V FR Viscoelastic Foam

Physical Properties:

Color	Pink
Density (ASTM D 3574 – A)	5.8 – 6.2 lb/ft³
IFD (ASTM D 3574 – B1)	28 – 34 lbf
Air Flow (ASTM D 3574 – G)	0.2 – 1.0 cfm
Tensile Strength (ASTM D 3574 – E)	> 14 psi
Tear Strength (ASTM D 3574 – F)	> 1.3 lbf/in
Elongation (ASTM D 3574 – E)	> 155 %

Flammability:

California TB 117-2013 Section 3	Pass
---	-------------

Our technical advice, whether verbal or in writing, is given in good faith but Bergad Inc. gives no warranty; express or implied, and all products are sold upon condition that purchasers will make their own tests to determine the quality and suitability of the product for their particular application and circumstances. Bergad Inc. shall be in no way responsible for the proper use and service of the product, nor for the safeguarding of personnel or property, all of which is the duty of the user. Any information or suggestions are without warranty of any kind and purchasers are solely responsible for any loss arising from the use of such information or suggestions. No information or suggestions given by us shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Before using any of our products, users should familiarize themselves with the relevant Technical and SDS provided by Bergad Inc.