

ENVIRONMENTAL OPEN CELL FOAM

Dated 9/2/2017 Revision 1

Product Description:

Unless otherwise stated, tested according to ASTM-D3574. Flammability tests are performed under controlled laboratory conditions. Polyurethane foam should be stored and handled with care. It should be kept away from sources of heat and flame at all times.

Physical Properties

| | |
|----------|---|
| Color | Black |
| Density | 1.60 |
| ILD | 40-50 lbs per 50 square inches, sample size 15"x15"x4" |
| Porosity | Off Scale |

Flammability Not Applicable

Mechanical Properties

| | |
|---------------|----------------|
| Tensile | Not Applicable |
| Tear | Not Applicable |
| Elongation | Not Applicable |
| Antimicrobial | Pass |
| Dynamic Flex | Not Applicable |

Our technical advice, whether verbal or in writing, is given in good faith but Bergad Inc. gives no warranty; express or implied, and all products are sold upon condition that purchasers will make their own tests to determine the quality and suitability of the product for their particular application and circumstances. Bergad Inc. shall be in no way responsible for the proper use and service of the product, nor for the safeguarding of personnel or property, all of which is the duty of the user. Any information or suggestions are without warranty of any kind and purchasers are solely responsible for any loss arising from the use of such information or suggestions. No information or suggestions given by us shall be deemed to be a recommendation to use any product in conflict with any existing patent rights. Before using any of our products, users should familiarize themselves with the relevant Technical and MSDS provided by Bergad Inc.