The FOAM FACTORY

17500 23 Mile Road
Macomb, MI 48044
Tel: (586) 627-3626
Fax: (586) 627-5830
www.thefoamfactory.com

Product General and Technical Information

Date: 12/10/2014 Name: Acoustic Foam

General Information
Acoustic foam is a specialty product with a medium feel. This foam is specially formulated (extra additives) for acoustical sound-deadening applications. Common applications include acoustic treatment, sound deadening and sound filtering. Available in 12 different colors, its typical life is 5 to 10 years.

Property	Test Method	Values
Density (LB/Cubic Ft.)	ASTM D 3574	1.2
25% ILD (LB)	ASTM D 3574	45
Support Factor (65%/25% Min.)	ASTM D 3574	1.90
Tensile (PSI) Min.	ASTM D 3574	13.0
Elongation (%) Min.	ASTM D 3574	200
Tear (PPI) Min.	ASTM D 3574	1.30
Resiliency (%) Min.	ASTM D 3574	35
Fire Retardant Classification	CA TB #117 ASTM E84	Pass Class A (Self Extinguishing)
Contains Fire Retardant Additives	- - -	Yes Contains NO PBDEs

All values reported are typical values. We cannot guarantee the applicability or the accuracy of this information or the suitability of the product for any particular purpose. This product is sold without warranty, expressed or implied. (Unless stated otherwise.) Buyer assumes all responsibility for loss or damage arising from the handling and use of this product, whether done in accordance with directions or not. Statements concerning the possible use of this product are not intended as recommendation to use this product in the infringement of any patent.

Copyright © 1997-2020 The Foam Factory. All rights reserved.